





**Features**

- Contains transducer electronic data sheet (IEEE 1451 - TEDS)
- Self-identifying
- Corrosion resistant
- Ground isolated
- Hermetic seal
- ESD protection
- Reverse wiring protection
- Mounts in any orientation



**Benefits**

- Simplifies troubleshooting
- Reduces safety risks - no more climbing on machines to verify connections
- Reduces costs for set-up and tear-down
- No need to recalibrate replacement units - data acquisition system will recalibrate itself
- Designed to integrate with wireless transmitters and receivers
  - eliminates long cables
  - reduces installation, maintenance and upgrade costs of measurement and control systems

**Model ED-787A  
TEDS low profile, general purpose  
accelerometer**

**Dynamic**

Sensitivity, ±10%, 25°C.....	100 mV/g
Acceleration range .....	80 g peak
Amplitude nonlinearity.....	1%
Frequency response:	
±10%.....	1.0 - 5,000 Hz
±3 dB .....	0.7 - 10,000 Hz
Resonance frequency.....	22 kHz
Transverse sensitivity, max.....	5% of axial
Temperature response.....	-50°C   -5%
	+120°C   +5%

**Electrical**

Power requirement: voltage source .....	18 - 30 VDC
current regulating diode .....	2 - 10 mA
Electrical noise, equiv. g:	
Broadband 2.5 Hz to 25 kHz.....	700 µg
Spectral 10 Hz.....	10 µg/√Hz
100 Hz.....	5 µg/√Hz
1000 Hz.....	5 µg/√Hz
Output impedance, max. ....	100 Ω
Bias output voltage.....	12 VDC
Grounding.....	case isolated, internally shielded

**Environmental**

Temperature range <sup>1</sup> .....	-50 to 120°C
Vibration limit.....	500 g
Shock limit, min. ....	5,000 g
Electromagnetic sensitivity, equiv. g, max . ....	70 µg/gauss
Sealing .....	Hermetic
Base strain sensitivity, max .....	0.002 g/µstrain

**Physical**

Sensing element design .....	PZT ceramic / shear
Weight .....	150 grams
Case material.....	316L stainless steel
Mounting .....	1/4 - 28 captive hex head screw with 0.046" diameter safety wire hole
Output connector.....	2 pin, MIL-C-5015 style
Mating connector .....	R6 type
Recommended cabling.....	J10 / J9T2A

Connector pin shell	Function	Cable conductor color
A	ground	shield
B	power/ signal	white
	common	black

Accessories supplied: #80165-01 captive hex head screw;

TEDS calibration data

Notes: <sup>1</sup>Temperature range is limited to -40°C to + 85°C when using the IEEE 1451 - TEDS function

Wilcoxon Research Inc  
21 Firstfield Rd  
Gaithersburg, MD 20878  
USA

Tel: 301 330 8811  
Fax: 301 330 8873

Email: sensors@wilcoxon.com

www.meggitt.com

**MEGGITT**  
smart engineering for  
extreme environments

